

Leak Tester

Model : HT-LTD

HT-LTD is a easy to use Leak Tester which facilitate the Leak Test by creating desired vacuum for specified time and provides convenience of observing for the Bubbles. Unique Air Operated Vacuum system provides Noise & Maintenance Free operation. These Vacuum Generators require atleast 3.5 Kg/cm² air pressure (to generate a vacuum of 680 mm of hg) and consume 44 - 66 L of air per minute for vacuum generation which is normally available in the Industry.



Application

The Leakage Tester used to check .

- Solid Filled / Air Filled packages
- Liquid Product Filled packages

for Leakage, capillary defects & pin holes

Features & Specification

- Digital Operating Console
- LCD Display & Key pad
- Vacuum Level setting
- Vacuum Holding Time setting
- In built Air operated Vacuum Generator
- Digital Vacuum Sensor
- Easy to Operate

Desiccators	Material of Construction	Chamber Shape	Chamber Type
D-RO-PC	Poly Carbonate	Round	Transparent Tank with 12 Inch Dia and 12 Inch Height
D-RC-AC	Acrylic	Cubical	Transparent Tank of 400x300x220 mm Inner dimension
D-CY-AC-400	Acrylic	Cylindrical	Transparent Cylindrical Tank with 300mm Dia . and 400mm Height . (True 360Deg Visibility)
D-CY-AC-600	Acrylic	Cylindrical	Transparent Cylindrical Tank with 300mm Dia . and 600mm Height . (True 360Deg Visibility)